



TC 6621 / 6622

Handheld temperature calibrator for
thermocouples or resistive probes
with memory

TC 6621 temperature calibrator measures or generates thermocouple temperatures (16 different types) and voltage at an accuracy of 0.02%. TC 6622 temperature calibrator measures or generates RTD temperatures (12 different types) and resistance at an accuracy of 0.02%.

Description

Easy-to-use and equipped with a large graphical display, TC temperature calibrators are the perfect field tools for easy and quick maintenance and commissioning of temperature transmitters and probes.

TC 6621 temperature calibrator measures or generates thermocouple temperatures (16 different types) and voltage at an accuracy of 0.02%.

TC 6622 temperature calibrator measures or generates RTD temperatures (12 different types) and resistance at an accuracy of 0.02%.

With a very low temperature coefficient (10 ppm/°C in thermocouples and 7ppm/°C in resistance), IP54 protection and robust design, TC calibrators are suitable for onsite use even in demanding environmental conditions. They are widely used in the energy field, engineering sector, metal industry and automotive field.

TC calibrators use a graphical interface making programming and reading easier, under graphical or test format. Due to memory feature (10,000 values) and extended functionalities (square root, steps, synthesizer, statistical functions...), TC are well adapted to different process job procedures and ensure full data traceability as well as advanced data exploitation. Use them together with DATACAL calibration software to display, manage data and issue your own customized calibration certificates.

TC calibrators are delivered with 4 alkaline AA batteries in standard. The optional battery charger used a rechargeable battery.

Key features:

- High accuracy: 0.02% reading with an adjustable resolution of 1 μ V (TC 6621) and 1 m Ω (TC 6622)
- Values displayed in °C, °F, mV and Ω
- Low temperature coefficient: 10 ppm /°C for thermocouples and 7 ppm/°C for resistance
- Measurements with HOLD function
- Simulation of ramps, preprogrammed steps and synthesizer values
- Correction of calibrated sensors
- Display of minimum, maximum and average value
- Backlight
- 10,000 values stored and displayed graphically

Specifications

Specifications and performances of TC 6621 @23°C ±5°C

DC voltage

| Function | Range | Res. | Accuracy / 1 year | Measuring range |
|----------|--------|------|-------------------|-----------------|
| IN | 100 mV | 1 µV | 0.020% RDG + 3 µV | -10 mV / 100 mV |
| OUT | 80 mV | 1 µV | 0.020% RDG + 3 µV | -9.5 mV / 80 mV |

Temperature coefficient < 15 ppm/°C beyond reference domain

Thermocouples: Measurement and simulation

| Type | Input range | Resolution | Accuracy / 1 year (Measurement) | Output range | Resolution | Accuracy / 1 year (Simulation) |
|------|---|--------------------------------------|---|---|----------------------------|--|
| K | -250 to -200°C -200 to -120°C -120 to 0°C 0 to +1372°C | 0.2°C 0.1°C 0.05°C 0.05°C | 0.90°C 0.3°C 0.02% RDG + 0.12°C 0.02% RDG + 0.11°C | -240 to -50°C -50 to +120°C +120 to +1372°C | 0.2°C 0.1°C 0.05°C | 0.8°C 0.3°C 0.02% RDG + 0.11°C |
| T | -250 to -200°C -200 to -50°C -50 to +400°C | 0.2°C 0.05°C 0.05°C | 0.8°C 0.25°C 0.02% RDG + 0.09°C | -240 to -100°C -100 to -40°C -40 to +400°C | 0.2°C 0.05°C 0.05°C | 0.5°C 0.25°C 0.02% RDG + 0.10°C |
| J | -210 to -200°C -200 to -120°C -120 to +60°C +60 to +1200°C | 0.05°C 0.05°C 0.05°C 0.05°C | 0.3°C 0.25°C 0.02% RDG + 0.11°C 0.02% RDG + 0.09°C | -210 to +50°C +50 to +500°C +500 to +1200°C | 0.05°C 0.05°C 0.05°C | 0.35°C 0.02% RDG + 0.11°C 0.02% RDG + 0.09°C |
| E | -250 to -200°C -200 to -100°C -100 to +450°C +450 to | 0.1°C 0.05°C 0.05°C 0.05°C | 0.55°C 0.2°C 0.02% RDG + 0.07°C 0.02% RDG + 0.05°C | -240 to -100°C -100 to +40°C +40 to +1000°C | 0.1°C 0.1°C 0.05°C | 0.55°C 0.2°C 0.02% RDG + 0.06°C |

| | | | | | | |
|-----------|--|------------------------------------|--|--|--------------------------|---|
| | 1000°C | | | | | |
| R | -50 to +150°C +150 to +550°C +550 to 1768°C | 0.5°C 0.2°C 0.1°C | 0.95°C 0.4°C 0.02% RDG + 0.3°C | -50 to +350°C +350 to +900°C 900°C to +1768°C | 0.5°C 0.2°C 0.1°C | 0.95°C 0.4°C 0.02% RDG + 0.3°C |
| S | -50 to +150°C +150 to +550°C +550 to +1768°C | 0.5°C 0.2°C 0.1°C | 0.85°C 0.02% RDG + 0.4°C 0.02% RDG + 0.3°C | -50 to +350°C +350 to 900°C +900 to +1768°C | 0.5°C 0.2°C 0.1°C | 0.9°C 0.02% RDG + 0.4°C 0.02% RDG + 0.3°C |
| B | +400 to +900°C +900 to +1820°C | 0.2°C 0.1°C | 0.95°C 0.5°C | +400 to +850°C +850 to +1820°C | 0.2°C 0.1°C | 0.95°C 0.5°C |
| U | -200 to -100°C -100 to +600°C | 0.05°C 0.05°C | 0.35°C 0.2°C | -200 to -70°C -70 to +600°C | 0.05°C 0.05°C | 0.35°C 0.2°C |
| L | -200 to -100°C -100°C to +900°C | 0.05°C 0.05°C | 0.3°C 0.2°C | -200 to -70°C -70 to +900°C | 0.05°C 0.05°C | 0.3°C 0.25°C |
| C | -20 to +900°C +900 to 2310°C | 0.1°C 0.1°C | 0.3°C 0.02% RDG + 0.15°C | -20 to +900°C +900 to 2310°C | 0.1°C 0.1°C | 0.35°C 0.02% RDG + 0.15°C |
| N | -240 to -190°C -190 to -110°C -110 to +0°C +0 to +1300°C | 0.2°C 0.1°C 0.05°C 0.05°C | 0.6°C 0.25°C 0.15°C 0.02% RDG + 0.07°C | -240 to +10°C +10 to +250°C +250 to +1300°C | 0.2°C 0.1°C 0.05°C | 0.9°C 0.2°C 0.02% RDG + 0.09°C |
| Platine | -100 to +1400°C | 0.05°C | 0.3°C | -100 to +1400°C | 0.05°C | 0.35°C |
| Mo | +0 to +1375°C | 0.05°C | 0.02% RDG + 0.1°C | +0 to +1375°C | 0.05°C | 0.25°C |
| NiMo/NiCo | -50 to +1410°C | 0.05°C | 0.02% RDG + 0.35°C | -50 to +1410°C | 0.05°C | 0.02% RDG + 0.35°C |

Thermocouples G, D: For specifications, refer to the instruction manual (Available on request)
Accuracy is given for reference @ 0°C.

When using the internal reference junction (except couple B) add an additional uncertainty of
0.3 °C at 0 °C.

It is possible (thermocouple B excepted) to choose by programming the cold junction
localization: External at 0°C, internal (temperature compensation of instrument's terminals) or

manually entered.

Temperature coefficient: <10% of accuracy /°C

Specifications and performances of TC 6622 @23°C ±5°C

Resistance

| Function | Range | Resolution | Accuracy / 1 year | Notes |
|---------------------|--------------------|---------------------|--------------------------------------|--------------------------------------|
| IN | 400 Ω | 1 mΩ | 0.012% RDG + 10 mΩ | Automatic detection: 2, 3 or 4 wires |
| 3600 Ω | 10 mΩ | 0.012% RDG + 100 mΩ | Automatic detection: 2, 3 or 4 wires | |
| OUT | 400 Ω (DC current) | 1 mΩ | 0.012% RDG + 30 mΩ | Acceptable current: 0.1 to 1 mA |
| 3550 Ω (DC current) | 10 mΩ | 0.012% RDG + 300 mΩ | Acceptable current: 0.1 to 1 mA | |

Connection in resistance and RTDs through banana plugs or 4-pin round connector

Temperature coefficient: < 7 ppm/°C beyond reference domain

Rising time in simulation: < 1 ms

R internal: < 1 Ω

Noise VLF < 1 mV (@ F < 100 Hz)

Resistive probes: Measurement and simulation

| Sensor | Range (Input and Output) | Resolution | Accuracy / 1 year (Measurement) | Accuracy / 1 year (Simulation) |
|----------------------------|--------------------------|------------|---------------------------------|--------------------------------|
| Pt50 ($\alpha = 3851$) | -220°C to +850°C | 0.01°C | 0.012% RDG + 0.06°C | 0.012% RDG + 0.18°C |
| Pt100 ($\alpha = 3851$) | -220°C to +850°C | 0.01°C | 0.012% RDG + 0.05°C | 0.012% RDG + 0.12°C |
| Pt100 ($\alpha = 3916$) | -200°C to +510°C | 0.01°C | 0.012% RDG + 0.05°C | 0.012% RDG + 0.12°C |
| Pt100 ($\alpha = 3926$) | -210°C to +850°C | 0.01°C | 0.012% RDG + 0.05°C | 0.012% RDG + 0.12°C |
| Pt200 ($\alpha = 3851$) | -220°C to +120°C | 0.01°C | 0.012% RDG + 0.12°C | 0.012% RDG + 0.33°C |
| Pt500 ($\alpha = 3851$) | -220°C to +1200°C | 0.01°C | 0.012% RDG + 0.07°C | 0.012% RDG + 0.18°C |
| Pt1000 ($\alpha = 3851$) | -220°C to +760°C | 0.01°C | 0.012% RDG + | 0.012% RDG + |

| | | | 0.05°C | 0.08°C |
|---------------------------|-----------------|--------|---------------------|---------------------|
| Ni100 ($\alpha = 618$) | -60°C to 180°C | 0.01°C | 0.012% RDG + 0.03°C | 0.012% RDG + 0.08°C |
| Ni120 ($\alpha = 672$) | -40°C to +205°C | 0.01°C | 0.012% RDG + 0.03°C | 0.012% RDG + 0.08°C |
| Ni1000 ($\alpha = 618$) | -60°C to +180°C | 0.01°C | 0.012% RDG + 0.03°C | 0.012% RDG + 0.08°C |
| Cu10 ($\alpha = 427$) | -50°C to 150°C | 0.01°C | 0.012% RDG + 0.18°C | 0.012% RDG + 0.1°C |
| Cu50 ($\alpha = 428$) | -50°C to +150°C | 0.01°C | 0.012% RDG + 0.06°C | 0.012% RDG + 0.15°C |

Resistive probes measurements in 2, 3 or 4 wires: automatic recognition of number of connected wires, with indication on screen

Accuracies are given for 4-wire mounted probes

Take into account particular error of temperature sensor used and implementation conditions

Measuring current: 0.65 mA

Simulation current: 0.1 mA to 1mA

Minimal current pulse duration: < 1 ms

Temperature coefficient: < 10% of accuracy /°C

Further features

| | |
|---|--|
| Scaling in measurement and simulation modes | This function allows sensors to be corrected after a calibration. Scaling is performed using up to 10 segments, in order to fit with the real calibrated value. |
| Calibrated sensors | A database can be created to design curves for sensor s after calibration according to the corrections mentioned on a calibration report. |
| Data recording | Data are recorded either manually on event or automatically with programmable frequency. Data is stored with date and time and can be displayed as list or curve. |
| Statistical functions | Continuous display of average, minimum and maximum value of the signal under monitoring, as well as number of measurements. |
| Simple and cyclical ramp generation | Ramps can be generated by setting low and high dwell, rising and falling times, stabilization and delay times (1 to 3,600 s). Delay time enables a single user to launch the ramp and go to the control panel. |
| Steps simulation | This mode allows predefined values to be sent with programmable amplitude and frequency. |
| Synthesizer | This mode allows predefined values to be sent with programmable frequency. |

General specifications

| | |
|---------------------|---|
| Size | 157 x 85 x 45 mm |
| Weight | 306 g |
| Display | 160 x 160 pixel liquid crystal graphical display with backlite Display of result as table of values or trend curve |
| Power supply | 4 AA batteries 1.5 V or rechargeable Ni-Mh batteries with internal charger in option |
| Communication ports | USB |
| Storage capacity | 10,000 data with date and time into one or several acquisition bursts |

Environmental specifications

| | |
|----------------------------|---|
| Reference range | 23°C \pm 5°C (RH: 45 to 75% w/o condensing) |
| Operating reference range | -10 to 50°C (RH: 20 to 80% w/o condensing) |
| Limit operating range | -15°C to +55°C (RH: 10 to 80% w/o condensing) (70% at 55°C) |
| Storage temperature limits | -30°C to +60°C |
| Maximum height | 0 to 2,200 m |
| IP protection | IP54 according to EN60529 |

Safety specifications

Protections

- Electronic protection up to 250 V for 'voltage' wires
- Fuse protection for 'current' wires
- Protection against 'current' circuit breaking during inductive resistance measurements

Class

In accordance with EN 61010-1
Category II, pollution 2

Rated voltage

60 V

Chocks and vibrations

EN 61010-1

EMC conformity

Models and accessories

Instrument:

TC 6621 Handheld calibrator for thermocouples with memory
Delivered in standard with:

- User manual
- 4 AA batteries
- Protection sheath
- Carrying strap
- Factory test report

TC 6622 Handheld calibrator for resistive probes with memory
Delivered in standard with:

- User manual
- 4 AA batteries
- Protection sheath
- Carrying strap
- Factory test report

Probes for TC 6621:

| | |
|--------------|---|
| ER 48145-130 | Male compensated plug type T |
| ER 48145-140 | Male compensated plug type J |
| ER 48145-150 | Male compensated plug type S |
| ER 48145-160 | Male compensated plug type K |
| ACC-A-R | Male compensated plug type LNRBEUC or D |
| T101 | Flexible type K sensor |
| T102 | Rigid K type sensor |
| T104 | Soft K sensor |
| T105 | Penetration K sensor |
| T106 | Surface K sensor |
| T703A | Surface temp. sensor K couple |
| T704 | Surface K sensor + springplate |

Probes for TC 6622:

ER48493-000 4-pin LEMO connector for Pt100*
S101E Pt100 environment sensor LEMO connector
S102E Pt100 immersion sensor LEMO connector
S103E Flexible housing sensor LEMO connector
*This accessory is necessary for RTDs with bare wires

Accessories:

AC6908 Soft carrying case for hand-held instruments
AN6011 Charger + batteries for hand-held instruments
ER 49519-000 USB cable mini B



Software:

DATA CAL TCTM Calibration software for TC / TM series
Supplied with USB cable mini B

Certification:

QMA11EN COFRAC certificate of calibration
With all relevant data points where the device has been tested

Packing information:

Size 157 x 85 x 45 mm
Weight without packing 306 g